



JUNCTION BOX

Abox-i 025-L/sw



Abox-i 025-L/sw

Junction box

CUSTOMIZABLE

80 x 80 x 52 mm
Article number: 49190201

Junction box - Industrial Quality - acc. DIN EN 60670 (VDE 0606), Ui=690V, weathering-proof, shock-proof, halogen-free, with self-sealing, soft inlet membranes, M20, seal range 2 - 16 mm

black, without terminal



Technical data

Measures

Width:	80 mm
Length:	80 mm
Height:	52 mm

Material

Base:	polycarbonate, membrane out of TPE
Cover:	polycarbonate, glass fiber- reinforced

Other attributes

Entries:	6
Rated cross section:	2,5 mm²
Tackable:	No
Rated insulation voltage AC:	690 V

Accessory

AST M20
KVR M20-GDB
KVR M20
GMU PA M20
ADR M20
WST M20
WNI M20
VST M20
VSS PA M20
SNI M20
BST M20
KS M20
HandyQuick SQ 52
HandyQuick SQ 32
HandyClip VC 21
HandyClip VC 20
HandyGrip VG 21 w



JUNCTION BOX

Abox-i 025-L/sw

Explosion safety:	none
Fire protection:	none
sealable:	Yes
Weatherproof:	Yes
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Ingress protection:	IP65 - acc. EN 60529 / DIN VDE 0470-1
Equiptment:	None
Color:	black

Environmental attributes

Ambient temperature (24 h):	60 °C
Ambient temperature (max.):	80 °C
Ambient temperature (min.):	-35 °C
Max. rel. humidity at 25° C (short Therm):	95%
Max. rel. humidity at 40° C:	50%

HandyGrip VG 20 w

HandyGrip VG 21

HandyGrip VG 20

KVR M20-GDB/MGM

VST M20-or

AST M20-or

DMS M20

KVR M20-MGM

DMS M20/sw

RST M20

HandyQuick SQ51

HandyQuick SQ81

HandyQuick SQ 31