



METER HOUSING

AKi-Z 3



AKi-Z 3

Meter housing

CUSTOMIZABLE

300 x 450 x 210 mm
Article number: 75201101

Meter housing - Industrial Quality -, IP65 (when using the corresponding cable entry), with transparent cover, standard version sealable, with meter crosspiece fitted for triphase counter and meter fixing screws, with IP54 attachment bushes, sealing and insulating plugs

IP65
IP54

IK08



400V
AC



Technical data

Measures

Width:	300 mm
Length:	450 mm
Height:	210 mm

Material

Base:	polycarbonate, glass fiber- reinforced
Cover:	Polycarbonate, transparent
Sealing:	Polyurethane
Cover screw:	Polyamide 6, fiber-glass reinforced

Other attributes

Ingress protection:	IP65 - acc. EN 60529 / DIN VDE
---------------------	-----------------------------------



METER HOUSING

AKi-Z 3

0470-1

Fire protection:	none
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes

Environmental attributes

Ambient temperature (24 h):	60 °C
Ambient temperature (max.):	80 °C
Ambient temperature (min.):	-35 °C
Max. rel. humidity at 25° C (short Therm):	95%
Max. rel. humidity at 40° C:	50%