



METER HOUSING

# AKi-Z 403-eHZ



## AKi-Z 403-eHZ

### Meter housing

#### CUSTOMIZABLE

300 x 600 x 210 mm  
Article number: 75211001

Meter housing - Industrial Quality -, IP65 (when using the corresponding cable entry), with transparent cover, standard version sealable, with assembled BKE-I for electronic domestic supply meter, standard version sealable consumer space at the top, with 35 mm standard rails and PE/N double terminals, standard version sealable consumer space at the bottom, with 35 mm standard rails and 5-pole HA terminal 25/16 mm², with IP54 attachment bushes, sealing and insulating plugs



## Technical data

### Measures

|         |        |
|---------|--------|
| Width:  | 300 mm |
| Length: | 600 mm |
| Height: | 210 mm |

### Material

|              |                                              |
|--------------|----------------------------------------------|
| Base:        | polycarbonate,<br>glass fiber-<br>reinforced |
| Cover:       | Polycarbonate,<br>transparent                |
| Sealing:     | Polyurethane                                 |
| Cover screw: | Polyamide 6,<br>fiber-glass<br>reinforced    |



## METER HOUSING

# AKi-Z 403-eHZ

### Other attributes

|                     |                                             |
|---------------------|---------------------------------------------|
| Ingress protection: | IP65 - acc. EN<br>60529 / DIN VDE<br>0470-1 |
| Fire protection:    | none                                        |
| Heavy metals-free:  | Yes                                         |
| PVC-free:           | Yes                                         |
| Silicone-free:      | Yes                                         |

### Environmental attributes

|                                               |        |
|-----------------------------------------------|--------|
| Ambient temperature (24 h):                   | 60 °C  |
| Ambient temperature (max.):                   | 80 °C  |
| Ambient temperature (min.):                   | -35 °C |
| Max. rel. humidity at 25° C (short<br>Therm): | 95%    |
| Max. rel. humidity at 40° C:                  | 50%    |