



METER HOUSING

AKi-Z 502



AKi-Z 502

Meter housing

CUSTOMIZABLE

300 x 750 x 210 mm
Article number: 75250201

Meter housing - Industrial Quality -, IP65 (when using the corresponding cable entry), with transparent cover, standard version sealable, with meter plate for triphase counter and fixing screws, additional connection space 300 mm at the bottom, with 35 mm standard rails, with IP54 attachment bushes, sealing and insulating plugs



Technical data

Measures

Width:	300 mm
Length:	750 mm
Height:	210 mm

Material

Base:	polycarbonate, glass fiber-reinforced
Cover:	Polycarbonate, transparent
Sealing:	Polyurethane
Cover screw:	Polyamide 6, fiber-glass reinforced

Other attributes

Ingress protection:	IP65 - acc. EN
---------------------	----------------



METER HOUSING

AKi-Z 502

60529 / DIN VDE
0470-1

Fire protection:	none
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes

Environmental attributes

Ambient temperature (24 h):	60 °C
Ambient temperature (max.):	80 °C
Ambient temperature (min.):	-35 °C
Max. rel. humidity at 25° C (short Therm):	95%
Max. rel. humidity at 40° C:	50%