



METER HOUSING

AKi-Z 511 KK



AKi-Z 511 KK

Meter housing

CUSTOMIZABLE

300 x 750 x 210 mm
Article number: 75851101

Meter housing - Industrial Quality -, IP65 (when using the corresponding cable entry), cover grey, standard version sealable, with transparent hinged window, with meter crosspiece fitted for triphase counter and meter fixing screws, with additional hinged window, with 35 mm standard rails for installing a selective main switch, incl. 2 single pole HA terminals 25/16 mm² for N and PE, with additional connection space 150 mm in output area, with 35 mm standard rails, with IP54 attachment bushes, twist nipple, sealing and insulating plugs



Technical data

Measures

Width:	300 mm
Length:	750 mm
Height:	210 mm

Material

Base:	polycarbonate, glass fiber- reinforced
Cover:	polycarbonate, glass fiber- reinforced
Sealing:	Polyurethane
Cover screw:	Polyamide 6, fiber-glass



METER HOUSING

AKi-Z 511 KK

reinforced

Other attributes

Fire protection:	none
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Ingress protection:	IP20 - acc. EN 60529 / DIN VDE 0470-1

Environmental attributes

Ambient temperature (24 h):	60 °C
Ambient temperature (max.):	80 °C
Ambient temperature (min.):	-35 °C
Max. rel. humidity at 25° C (short Therm):	95%
Max. rel. humidity at 40° C:	50%