

MSR100 Series Safety Relays

Features

- Category 4 per EN954-1
- Removable or Fixed Terminals
- Monitored Manual or Automatic Reset

Model Key

- T = Automatic / Manual Reset
- R = Monitored Manual Reset
- P = Removable Terminals

Approvals

- C-Tick, CE, cULus, BG



Stop Category 0 Relays

Inputs	Safety Outputs	Auxiliary Outputs	Terminals	Supply Voltage	Model	Cat. No.		
1 N.C.	3 N.O.	1 N.C.	Fixed	24V AC/DC	MSR117T	440R-B23211		
1 N.C., LC (MSR126T)	2 N.O.	None	Fixed	24V AC/DC	MSR126T	440R-N23117		
				110V AC	MSR126T	440R-N23116		
				230V AC	MSR126T	440R-N23115		
				24V AC/DC	MSR126R	440R-N23123		
				110V AC	MSR126R	440R-N23122		
				230V AC	MSR126R	440R-N23121		
2 N.C. (MSR126.IT)	2 N.O.	None	Fixed	24V AC/DC	MSR126.IT	440R-N23114		
				110V AC	MSR126.IT	440R-N23113		
				230V AC	MSR126.IT	440R-N23112		
				24V AC/DC	MSR126.IR	440R-N23120		
				110V AC	MSR126.IR	440R-N23119		
				230V AC	MSR126.IR	440R-N23118		
1 N.C., 2 N.C., or LC	3 N.O.	1 N.C.	Fixed	24V AC/DC	MSR127T	440R-N23126		
				110V AC	MSR127T	440R-N23125		
				230V AC	MSR127T	440R-N23124		
				24V AC/DC	MSR127R	440R-N23129		
				110V AC	MSR127R	440R-N23128		
				230V AC	MSR127R	440R-N23127		
			Removable	24V AC/DC	MSR127TP	440R-N23132		
				110V AC	MSR127TP	440R-N23131		
				230V AC	MSR127TP	440R-N23130		
				24V AC/DC	MSR127RP	440R-N23135		
1 N.C., 2 N.C., LC, SM	7 N.O.	4 N.C., 2 PNP, Solid State	Removable	24V AC/DC	MSR142RTP	440R-G23216		
				110V AC	MSR142RTP	440R-G23215		
				230V AC	MSR142RTP	440R-G23214		
1 N.C. or 2 N.C. or LC or SM	3 N.O.	2 N.C., 2 PNP Solid State	Removable	24V AC/DC	MSR131RTP	440R-C23139		
				110V AC	MSR131RTP	440R-C23137		
				230V AC	MSR131RTP	440R-C23136		